



SAFETY DATA SHEET
KÖSTER NB Super Elastik BEYAZ - Powder Component
According to regulation (EU) No. 2015/830

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name KÖSTER NB Super Elastik BEYAZ - Powder Component

Product number 0201-a

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cement based waterproofing product with two component.

1.3. Details of the supplier of the safety data sheet

Supplier KÖSTER YAPI KİMYASALLARI İNŞ. SAN. VE TİC. A.Ş.
GEBKİM Kimya İhtisas OSB, Atatürk Bulvarı No:6, Dilovası, 41455 Kocaeli -Turkey
Tel: +90 (262) 754 2020
www.koster.com.tr

Contact person Mazlum BUDAK (Mr) - Quality Control Manager
bilgi@koster.com.tr

1.4. Emergency telephone number

Emergency telephone Köster: +90 262 754 2020

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

KÖSTER NB Super Elastik BEYAZ - Powder Component

Precautionary statements

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains Cement, portland, chemicals

2.3. Other hazards

The substance content classified as PBT or vPvB does not exceed 0.1%.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| | |
|------------------------------------|----------------------|
| Cement, portland, chemicals | 25-40% |
| CAS number: 65997-15-1 | EC number: 266-043-4 |
| Exempt from REACH regulation. | |

Classification

Skin Irrit. 2 - H315
 Eye Dam. 1 - H318
 Skin Sens. 1B - H317
 STOT SE 3 - H335

The full text for all hazard statements is displayed in Section 16.

Ingredient notes Exempt from REACH regulation.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.

Ingestion Rinse mouth thoroughly with water. If in doubt, get medical attention promptly. Do not induce vomiting unless under the direction of medical personnel.

Skin contact Remove contaminated clothing and rinse skin thoroughly with water. Wash contaminated clothing before reuse. Get medical attention promptly if symptoms occur after washing. If in doubt, get medical attention promptly.

Eye contact Rinse with water. Do not rub eye. Continue to rinse for at least 10 minutes. Remove any contact lenses and open eyelids wide apart. Get medical attention if any discomfort continues.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

KÖSTER NB Super Elastik BEYAZ - Powder Component

| | |
|----------------------------|---|
| General information | The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
| Inhalation | Dust may irritate the respiratory system. |
| Ingestion | Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. |
| Skin contact | Redness. Irritating to skin. May cause sensitisation or allergic reactions in sensitive individuals. |
| Eye contact | Causes serious eye irritation. Pain. Itchiness. Redness. |

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire. Use foam, carbon dioxide, dry powder or water fog to extinguish.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Avoid contact with skin, eyes and clothing. Do not handle broken packages without protective equipment. Wash thoroughly after dealing with a spillage.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

KÖSTER NB Super Elastik BEYAZ - Powder Component

Methods for cleaning up

Clear up spills immediately and dispose of waste safely. Avoid generation and spreading of dust. Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into suitable waste disposal containers and seal securely. If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Leave small quantities to evaporate, if safe to do so.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Obtain special instructions before use. Wear protective clothing as described in Section 8 of this safety data sheet. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid breathing dust. Avoid handling which leads to dust formation.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.

Storage class

Chemical storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Quartz (SiO₂), Crystalline Silica

Long-term exposure limit (8-hour TWA): OSHA 0.05 mg/m³

Long-term exposure limit (8-hour TWA): TLV:Threshold Limit Values 1 mg/m³

Cement, portland, chemicals

Long-term exposure limit (8-hour TWA): TLV:Threshold Limit Values 10 mg/m³

OSHA = Occupational Safety and Health Administration.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Use mechanical ventilation if there is a risk of handling causing formation of airborne dust.

KÖSTER NB Super Elastik BEYAZ - Powder Component

| | |
|--|---|
| Eye/face protection | Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. |
| Hand protection | Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. When used with mixtures, the protection time of gloves cannot be accurately estimated. It is recommended that gloves are made of the following material: Butyl rubber. Nitrile rubber. Polyvinyl chloride (PVC). |
| Hygiene measures | Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. |
| Respiratory protection | If ventilation is inadequate, suitable respiratory protection must be worn. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m ³ . Particulate filter, type P1. |
| Environmental exposure controls | Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|-----------------------------|
| Appearance | Powder. |
| Colour | White. |
| Odour | Odourless. |
| Odour threshold | No information available. |
| pH | No information available. |
| Melting point | No information available. |
| Initial boiling point and range | No information available. |
| Flash point | No information available. |
| Evaporation rate | No information available. |
| Evaporation factor | No information available. |
| Flammability (solid, gas) | No information available. |
| Upper/lower flammability or explosive limits | No information available. |
| Other flammability | No information available. |
| Vapour pressure | No information available. |
| Vapour density | No information available. |
| Relative density | No information available. |
| Bulk density | 1,1 - 1,3 g/cm ³ |
| Solubility(ies) | No information available. |
| Partition coefficient | No information available. |

KÖSTER NB Super Elastik BEYAZ - Powder Component

| | |
|----------------------------------|---------------------------|
| Auto-ignition temperature | No information available. |
| Decomposition Temperature | No information available. |
| Viscosity | No information available. |
| Explosive properties | No information available. |
| Oxidising properties | Not known. |

9.2. Other information

| | |
|----------------------------------|---------------------------|
| Refractive index | No information available. |
| Particle size | No information available. |
| Molecular weight | No information available. |
| Volatility | No information available. |
| Saturation concentration | No information available. |
| Critical temperature | No information available. |
| Volatile organic compound | No information available. |

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|-------------------|---|
| Reactivity | There are no known reactivity hazards associated with this product. |
|-------------------|---|

10.2. Chemical stability

| | |
|------------------|---|
| Stability | Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions. |
|------------------|---|

10.3. Possibility of hazardous reactions

| | |
|---|---|
| Possibility of hazardous reactions | No potentially hazardous reactions known. |
|---|---|

10.4. Conditions to avoid

| | |
|----------------------------|---|
| Conditions to avoid | There are no known conditions that are likely to result in a hazardous situation. |
|----------------------------|---|

10.5. Incompatible materials

| | |
|---------------------------|--|
| Materials to avoid | No specific material or group of materials is likely to react with the product to produce a hazardous situation. |
|---------------------------|--|

10.6. Hazardous decomposition products

| | |
|---|---|
| Hazardous decomposition products | Does not decompose when used and stored as recommended. |
|---|---|

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation

| | |
|----------------------------------|---------------------|
| Skin corrosion/irritation | Irritating to skin. |
|----------------------------------|---------------------|

Serious eye damage/irritation

| | |
|--------------------------------------|---------------------|
| Serious eye damage/irritation | Irritating to eyes. |
|--------------------------------------|---------------------|

Respiratory sensitisation

| | |
|----------------------------------|--|
| Respiratory sensitisation | Based on available data the classification criteria are not met. |
|----------------------------------|--|

KÖSTER NB Super Elastik BEYAZ - Powder Component

Skin sensitisation

Skin sensitisation Sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Irritation of nose, throat and airway.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Inhalation No adverse effects known.

Ingestion May cause stomach pain or vomiting.

Skin contact Redness. Irritating.

Eye contact Causes serious eye irritation. Redness. Irritation and redness, followed by blurred vision.

SECTION 12: Ecological information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Toxicity No information available.

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

12.4. Mobility in soil

Mobility No information available.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

KÖSTER NB Super Elastik BEYAZ - Powder Component

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

Uygulanamaz

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.
Health and Safety at Work etc. Act 1974 (as amended).
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

KÖSTER NB Super Elastik BEYAZ - Powder Component

| | |
|---|---|
| Abbreviations and acronyms used in the safety data sheet | ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. CAS: Chemical Abstracts Service. IMDG: International Maritime Dangerous Goods. LC ₅₀ : Lethal Concentration to 50 % of a test population. LD ₅₀ : Lethal Dose to 50% of a test population (Median Lethal Dose). vPvB: Very Persistent and Very Bioaccumulative. |
| Classification abbreviations and acronyms | Skin Irrit. = Skin irritation Eye Dam. = Serious eye damage Skin Sens. = Skin sensitisation STOT SE = Specific target organ toxicity-single exposure |
| Revision comments | Revised classification. |
| Issued by | Mazlum Budak Sertifikalı GBF hazırlayıcısı Sertifika No: GBF01.35.06 Sertifika alım tarihi: 06.07.2019 |
| Revision date | 28/08/2020 |
| Revision | 5.0 |
| Supersedes date | 04/08/2011 |
| SDS number | 4800 |
| Hazard statements in full | H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation. |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.