



T 704 / 0206.ENG

KÖSTER® KD 2 Blitz

Reactive powder for sealing active leaks in a very short time

Product Description:

Turkish product name > KÖSTER Yıldırım Tozu

KÖSTER KD 2 is a highly reactive powder with extremely short setting time. KD 2 Blitz is used for sealing active water leaks simply by forcing the loose powder (by hand) to the leakage source and waiting a few seconds.

Applications:

- For sealing active water leaks
- For drying wet application surfaces in a short time
- To mix with cement based mortar to make them react faster and cure in a shorter period
- As a temporary seal and waterproof cracks prior to injection with injection resins

Instructions:

Job Conditions - Air and surface temperature for application must be +5°C to +30°C.

Surface Preparation - The surface has to be sound and solid.

Application – Rub in the KD 2 Blitz powder until the water stops flowing (app. 20 seconds).

Consumption:

Approx 1 lt space _____ 2 kg void



Packaging:

KÖSTER KD 2 Blitz _____ 5 kg pail



Cleaning of Tools:

Clean tools with water while material is still wet.

Storage:

Containers must be stored at +5°C to +30°C in tightly sealed containers. Keep out of direct sunlight, protect from water and freezing.

Shelf Life: 12 months.

Caution:

Powder component contains cement. Avoid contact with skin and eyes. Wear suitable protective clothing, gloves and eye / face protection. After contact with skin, wash immediately with plenty of water and soap. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. For additional references to safety-hazard warnings, regulations regarding the transport and waste management please refer to the relevant Material Safety Data Sheet.



T 704 / 0206.ENG

Legal Notes : This guide has been issued to provide details regarding the use and application of our products, which can be used in very wide and various areas and to demonstrate the general technical details. This information reflects the knowledge and expertise of our company and is of recommendation nature. Especially, the details regarding implementation and final use are provided with good will to cover the storage, handling and application of our products under normal and recommended conditions. Products, application surfaces, areas and application conditions vary in practice. Therefore, it is of utmost importance to make sure you are applying the right product, at the right conditions and places. Since KÖSTER cannot check how its products are used, it does not accept any responsibility regarding the results of the application and does not provide any guarantees. Information provided here or written/verbal information provided by KÖSTER employees should solely be considered as recommendation. KÖSTER employees to visit the application area do not create any supervisor responsibilities on our part. The product users (user) should test the suitability of the product they are planning to use for the respective application and purpose. KÖSTER has the right to modify its products without announcement. Acceptance of all orders is based on our current sale and transportation terms and conditions. Users should always consider the final version of the local Technical Sheet of the respective product, which can be obtained by applying to KÖSTER. Product users should act cautious and observe and protect their own interests and property rights. They are even obliged to act in this manner. This guide only covers KÖSTER products and is not valid for products of other companies. Only the written announcements of our company are valid regarding matters that require technical support provided by us. This technical document is valid until a new version is printed and supersedes all previous versions.

Revision Date: 30-11-2020