

SAFETY DATA SHEET KÖSTER KB-Pur 223 - A Component

According to regulation (EU) No. 2015/830

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name KÖSTER KB-Pur 223 - A Component

Product number 0411-a

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Waterproofing product

1.3. Details of the supplier of the safety data sheet

Supplier KÖSTER YAPI KİMYASALLARI İNŞ. SAN. VE TİC. A.Ş.

GEBKIM Kimya Ihtisas OSB, Atatürk Bulvarı No:6, Dilovası, 41455 Kocaeli -Turkey

Tel: +90 (262) 754 2020 www.koster.com.tr

Contact person Mazlum BUDAK (Mr) - Quality Control Manager

bilgi@koster.com.tr

1.4. Emergency telephone number

Emergency telephone Köster: +90 262 754 2020

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT RE 2 - H373

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms







Signal word Warning

Hazard statements H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure if swallowed or if

inhaled.

KÖSTER KB-Pur 223 - A Component

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed. P260 Do not breathe vapour/ spray.

P264 Wash contaminated skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P314 Get medical advice/ attention if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/ attention.
P337+P313 If eye irritation persists: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label information

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

xylene 10-20%

CAS number: 1330-20-7 EC number: 215-535-7 REACH registration number: 01-

2119488216-32-0000

Classification

Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical

personnel.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms

are severe or persist.

Ingestion Rinse mouth thoroughly with water. If in doubt, get medical attention promptly. Do not induce

vomiting unless under the direction of medical personnel.

Skin contact Rinse with water. Take off immediately all contaminated clothing and wash it before reuse.

Get medical attention promptly if symptoms occur after washing.

KÖSTER KB-Pur 223 - A Component

Eye contact Rinse with water. Get medical attention if any discomfort continues.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Vapours may cause headache, fatigue, dizziness and nausea. Vapours may cause

drowsiness and dizziness.

Ingestion May cause stomach pain or vomiting.

Skin contact Slightly irritating. May cause an allergic skin reaction.

Eye contact Irritating. Redness. Irritation and redness, followed by blurred vision.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-Suitable extinguishing media

extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

> Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or

explosion hazard.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Asphyxiating gases. Carbon dioxide (CO2). Carbon monoxide

(CO). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs,

notify appropriate authorities.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with

> skin, eyes and clothing. No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or

other sources of ignition near spillage.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Inform authorities if large amounts are involved. Large Spillages: Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Do not get in eyes, on skin, or on clothing. Persons susceptible to allergic reactions should not handle this product. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.

Storage class

Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

xylene

Long-term exposure limit (8-hour TWA): 50 ppm 221 mg/m³ Short-term exposure limit (15-minute): 100 ppm 442 mg/m³

8.2. Exposure controls

Protective equipment







KÖSTER KB-Pur 223 - A Component

Appropriate engineering

controls

 $\label{provide} \mbox{Provide adequate ventilation. Use explosion-proof general and local exhaust ventilation.}$

Ensure operatives are trained to minimise exposure.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with European Standard EN374. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Wear protective gauntlets made of the following

material: Polyvinyl chloride (PVC). Butyl rubber.

Other skin and body

protection

Wear apron or protective clothing in case of contact.

Hygiene measures Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.

Wash contaminated clothing before reuse.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

Environmental exposure

controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental

protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Tranparent

Odour Characteristic.

Odour threshold No information available.

pH No information available.

Melting point No information available.

Initial boiling point and range No information available.

Flash point 42 °C

Evaporation rate No information available.

Evaporation factor No information available.

Flammability (solid, gas) Flammable liquid and fluid

Upper/lower flammability or

explosive limits

No information available.

Other flammability No information available.

Vapour pressureNo information available.

Vapour density No information available.

Relative density No information available.

Bulk density 0,95 - 1,0 g/cm3

KÖSTER KB-Pur 223 - A Component

Solubility(ies) Organic Solvents

Partition coefficientNo information available.Auto-ignition temperatureNo information available.Decomposition TemperatureNo information available.

Viscosity 3000 mPa s @ °C

Explosive properties No information available.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

The following materials may react with the product: Oxidising agents.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Containers can burst violently or explode

when heated, due to excessive pressure build-up. Static electricity and formation of sparks

must be prevented.

10.5. Incompatible materials

Materials to avoid Oxidising agents. Acids - oxidising.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal

ATE dermal (mg/kg) 7,333.33

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 73.33

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Irritating to eyes.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Sensitising.

KÖSTER KB-Pur 223 - A Component

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

Based on available data the classification criteria are not met.

development

Specific target organ toxicity - single exposure

STOT - single exposureNot classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Inhalation Prolonged or repeated exposure to vapours in high concentrations may cause the following

adverse effects: May cause drowsiness or dizziness. Vapours may cause drowsiness and

dizziness.

Ingestion May cause stomach pain or vomiting.

Skin contact Slightly irritating. Redness.

Eye contact Causes serious eye irritation. Redness. Irritation and redness, followed by blurred vision.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target organs No specific target organs known.

SECTION 12: Ecological information

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have

hazardous effects on the environment.

12.1. Toxicity

Toxicity No information available.

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

12.4. Mobility in soil

Mobility No information available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

No data available.

assessment

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. This material and

its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out.

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

 UN No. (ADR)
 1139

 UN No. (IMDG)
 1139

UN No. (ICAO) 1139
UN No.(RID) Not applicable.

UN No. (ADN) Not applicable.

14.2. UN proper shipping name

Proper shipping name (ADR) COATING SOLUTION

Proper shipping name (IMDG) COATING SOLUTION

Proper shipping name (ICAO) Coating Solution

Proper shipping name (ADN) Not applicable.

Proper shipping name (RID) Not applicable.

Transport document NOT SUBJECT TO THE PROVISIONS OF ADR

description (ADR) - The product is packed in receptacles of less than 450 litres capacity.

- Exempted according to 2.2.3.1.5 (Viscous substance exemption)), 3, III, (D/E)

Transport document description (IMDG)

(NOT SUBJECT TO THE PROVISIONS OF IMDG CODE FOR THE MARKING, LABELLING

AND TESTING OF PACKAGES IN CHAPTERS 4.1, 5.2, AND 6.1.

- The product is packed in receptacles not exceeding 30 L capacity

- The following statement shall be included in the transport document:

"Transport in accordance with 2.3.2.5 of the IMDG Code."), 3, III

Transport document

description(IATA):

UN 1139 Coating solution, 3, III

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



Transport hazard class(es)

(ADN)

Not applicable.

RID Transport hazard

class(es) (RID)

Not applicable.

14.4. Packing group

ADR Packing Group

RID Packing Group Not applicable.

IMDG packing group III

ICAO packing group III

ADN packing group Not applicable.

14.5. Environmental hazards

Dangerous for the

environment

No.

No

30

Ш

Marine pollutant

Other information No supplementary information available

14.6. Special precautions for user

ADR transport category 3

Emergency Action Code •3YE

Hazard Identification Number

(ADR/RID)

Tunnel restriction code (D/E)

Special provisions (ADR) 640E

Limited quantities (ADR) 5L

Excepted quantities (ADR) E1

Classification code (ADR) F1

Mixed packing provisions

(ADR)

MP19

Packing instructions (ADR) P001, IBC03, LP01, R001

Special provisions for carriage V12

- Packages (ADR)

Special provisions for carriage S2

- Operation (ADR)

Orange plates 30

1139

Limited quantities (IMDG) 5L

KÖSTER KB-Pur 223 - A Component

Excepted quantities (IMDG) E1

Special provisions (IMDG) 955

Packing instructions (IMDG) P001, LP01

IBC packing instructions

(IMDG)

IBC03

Tank instructions (IMDG) T2

Tank special provisions

(IMDG)

TP1

EmS-No. (Fire)

F-E

EmS-No. (Spillage)

S-E

Stowage category (IMDG)

Α

Excepted quantities (IATA)

E1

Limited quantities (IATA)

10L Y344

PCA Excepted quantities

(IATA)

PCA packing instructions

(IATA)

60L

355

CAO packing instructions

PCA max net quantity (IATA)

366

(IATA)

CAO max net quantity (IATA) 220L

Special provisions (IATA) A3

ERG code (IATA) 3L

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

Uygulanamaz

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

Health and Safety at Work etc. Act 1974 (as amended).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by Mazlum Budak Sertifikalı GBF hazırlayıcısı Sertifika No: GBF01.35.06 Sertifika alım tarihi:

06.07.2019

Revision date 29/07/2020

Revision 1,0

Supersedes date 30/06/2017

SDS number 4993

Hazard statements in full H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure if swallowed or if

inhaled.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.