



**SAFETY DATA SHEET**  
**KÖSTER Ultraflex-2K A Component**  
According to regulation (EU) No. 2015/830

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name** KÖSTER Ultraflex-2K A Component  
**Product number** 0416 a

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** Waterproofing product

**1.3. Details of the supplier of the safety data sheet**

**Supplier** KÖSTER YAPI KİMYASALLARI İNŞ. SAN. VE TİC. A.Ş.  
GEBKİM Kimya Ihtisas OSB, Atatürk Bulvarı No:6, Dilovası, 41455 Kocaeli -Turkey  
Tel: +90 (262) 754 2020  
www.koster.com.tr

**Contact person** Mazlum BUDAK (Mr) - Quality Control Manager  
bilgi@koster.com.tr

**1.4. Emergency telephone number**

**Emergency telephone** Köster: +90 262 754 2020

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification (EC 1272/2008)**

**Physical hazards** Flam. Liq. 3 - H226  
**Health hazards** Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT RE 2 - H373  
**Environmental hazards** Not Classified

**2.2. Label elements**

**Hazard pictograms**



**Signal word** Warning

**Hazard statements** H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H373 May cause damage to organs through prolonged or repeated exposure if swallowed or if inhaled.

## KÖSTER Ultraflex-2K A Component

<b>Precautionary statements</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P233 Keep container tightly closed.</p> <p>P240 Ground and bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use non-sparking tools.</p> <p>P243 Take action to prevent static discharges.</p> <p>P260 Do not breathe vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P314 Get medical advice/ attention if you feel unwell.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	---

**Supplemental label information** EUH204 Contains isocyanates. May produce an allergic reaction.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

<b>xylene</b>		<b>10-20%</b>
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-0000
<b>Classification</b>		
Flam. Liq. 3 - H226		
Acute Tox. 4 - H312		
Acute Tox. 4 - H332		
Skin Irrit. 2 - H315		

The full text for all hazard statements is displayed in Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**General information** If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.

## KÖSTER Ultraflex-2K A Component

<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
<b>Ingestion</b>	Rinse mouth thoroughly with water. If in doubt, get medical attention promptly. Do not induce vomiting unless under the direction of medical personnel.
<b>Skin contact</b>	Rinse with water. Take off immediately all contaminated clothing and wash it before reuse. Get medical attention promptly if symptoms occur after washing.
<b>Eye contact</b>	Rinse with water. Get medical attention if any discomfort continues.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Vapours may cause headache, fatigue, dizziness and nausea. Vapours may cause drowsiness and dizziness.
<b>Ingestion</b>	May cause stomach pain or vomiting.
<b>Skin contact</b>	Slightly irritating. May cause an allergic skin reaction.
<b>Eye contact</b>	Irritating. Redness. Irritation and redness, followed by blurred vision.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard.
<b>Hazardous combustion products</b>	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Asphyxiating gases. Carbon dioxide (CO <sub>2</sub> ). Carbon monoxide (CO). Carbon monoxide (CO).

### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

## KÖSTER Ultraflex-2K A Component

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with skin, eyes and clothing. No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage.

#### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground.

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Inform authorities if large amounts are involved. Large Spillages: Absorb in vermiculite, dry sand or earth and place into containers.

#### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Do not get in eyes, on skin, or on clothing. Persons susceptible to allergic reactions should not handle this product. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

**Advice on general occupational hygiene** Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.

**Storage class** Flammable liquid storage.

#### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

**xylene**

## KÖSTER Ultraflex-2K A Component

Long-term exposure limit (8-hour TWA): 50 ppm 221 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): 100 ppm 442 mg/m<sup>3</sup>

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate ventilation. Use explosion-proof general and local exhaust ventilation. Ensure operatives are trained to minimise exposure.

#### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

#### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with European Standard EN374. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Wear protective gauntlets made of the following material: Polyvinyl chloride (PVC). Butyl rubber.

#### Other skin and body protection

Wear apron or protective clothing in case of contact.

#### Hygiene measures

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

#### Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

#### Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Tranparent
Odour	Characteristic.
Odour threshold	No information available.
pH	No information available.
Melting point	No information available.
Initial boiling point and range	No information available.
Flash point	42 °C
Evaporation rate	No information available.
Evaporation factor	No information available.
Flammability (solid, gas)	Flammable liquid and fluid
Upper/lower flammability or explosive limits	No information available.

## KÖSTER Ultraflex-2K A Component

<b>Other flammability</b>	No information available.
<b>Vapour pressure</b>	No information available.
<b>Vapour density</b>	No information available.
<b>Relative density</b>	No information available.
<b>Bulk density</b>	0,95 - 1,0 g/cm <sup>3</sup>
<b>Solubility(ies)</b>	Organic Solvents
<b>Partition coefficient</b>	No information available.
<b>Auto-ignition temperature</b>	No information available.
<b>Decomposition Temperature</b>	No information available.
<b>Viscosity</b>	1200 (dynamic), cP @ °C
<b>Explosive properties</b>	No information available.

### 9.2. Other information

#### SECTION 10: Stability and reactivity

##### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

##### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

##### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** The following materials may react with the product: Oxidising agents.

##### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.

##### 10.5. Incompatible materials

**Materials to avoid** Oxidising agents. Acids - oxidising.

##### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended.

#### SECTION 11: Toxicological information

##### 11.1. Information on toxicological effects

###### Acute toxicity - dermal

**ATE dermal (mg/kg)** 7,333.33

###### Acute toxicity - inhalation

**ATE inhalation (vapours mg/l)** 73.33

###### Skin corrosion/irritation

**Skin corrosion/irritation** Based on available data the classification criteria are not met.

###### Serious eye damage/irritation

## KÖSTER Ultraflex-2K A Component

<b>Serious eye damage/irritation</b>	Irritating to eyes.
<b><u>Respiratory sensitisation</u></b>	
<b>Respiratory sensitisation</b>	Based on available data the classification criteria are not met.
<b><u>Skin sensitisation</u></b>	
<b>Skin sensitisation</b>	Sensitising.
<b><u>Germ cell mutagenicity</u></b>	
<b>Genotoxicity - in vitro</b>	Based on available data the classification criteria are not met.
<b>Genotoxicity - in vivo</b>	Based on available data the classification criteria are not met.
<b><u>Carcinogenicity</u></b>	
<b>Carcinogenicity</b>	Based on available data the classification criteria are not met.
<b><u>Reproductive toxicity</u></b>	
<b>Reproductive toxicity - fertility</b>	Based on available data the classification criteria are not met.
<b>Reproductive toxicity - development</b>	Based on available data the classification criteria are not met.
<b><u>Specific target organ toxicity - single exposure</u></b>	
<b>STOT - single exposure</b>	Not classified as a specific target organ toxicant after a single exposure.
<b><u>Specific target organ toxicity - repeated exposure</u></b>	
<b>STOT - repeated exposure</b>	Not classified as a specific target organ toxicant after repeated exposure.
<b><u>Aspiration hazard</u></b>	
<b>Aspiration hazard</b>	Based on available data the classification criteria are not met.
<b>Inhalation</b>	Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: May cause drowsiness or dizziness. Vapours may cause drowsiness and dizziness.
<b>Ingestion</b>	May cause stomach pain or vomiting.
<b>Skin contact</b>	Slightly irritating. Redness.
<b>Eye contact</b>	Causes serious eye irritation. Redness. Irritation and redness, followed by blurred vision.
<b>Route of exposure</b>	Ingestion Inhalation Skin and/or eye contact
<b>Target organs</b>	No specific target organs known.

### SECTION 12: Ecological information

**Ecotoxicity** Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

#### 12.1. Toxicity

**Toxicity** No information available.

#### 12.2. Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** No information available.

## KÖSTER Ultraflex-2K A Component

### 12.4. Mobility in soil

**Mobility** No information available.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** No data available.

### 12.6. Other adverse effects

**Other adverse effects** Not known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** The generation of waste should be minimised or avoided wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

## SECTION 14: Transport information

### 14.1. UN number

**UN No. (ADR)** 1139

**UN No. (IMDG)** 1139

**UN No. (ICAO)** 1139

**UN No.(RID)** Not applicable.

**UN No. (ADN)** Not applicable.

### 14.2. UN proper shipping name

**Proper shipping name (ADR)** COATING SOLUTION

**Proper shipping name (IMDG)** COATING SOLUTION

**Proper shipping name (ICAO)** Coating Solution

**Proper shipping name (ADN)** Not applicable.

**Proper shipping name (RID)** Not applicable.

**Transport document description (ADR)** NOT SUBJECT TO THE PROVISIONS OF ADR  
 - The product is packed in receptacles of less than 450 litres capacity.  
 - Exempted according to 2.2.3.1.5 (Viscous substance exemption)), 3, III, (D/E)

**Transport document description (IMDG)** (NOT SUBJECT TO THE PROVISIONS OF IMDG CODE FOR THE MARKING, LABELLING AND TESTING OF PACKAGES IN CHAPTERS 4.1, 5.2, AND 6.1.  
 - The product is packed in receptacles not exceeding 30 L capacity  
 - The following statement shall be included in the transport document: "Transport in accordance with 2.3.2.5 of the IMDG Code."), 3, III

**Transport document description(IATA) :** UN 1139 Coating solution, 3, III

### 14.3. Transport hazard class(es)

**ADR/RID class** 3



## KÖSTER Ultraflex-2K A Component

<b>ADR/RID classification code</b>	F1
<b>ADR/RID label</b>	3
<b>IMDG class</b>	3
<b>ICAO class/division</b>	3
<b>ADN class</b>	3

### Transport labels



**Transport hazard class(es) (ADN)** Not applicable.

**RID Transport hazard class(es) (RID)** Not applicable.

### 14.4. Packing group

<b>ADR Packing Group</b>	III
<b>RID Packing Group</b>	Not applicable.
<b>IMDG packing group</b>	III
<b>ICAO packing group</b>	III
<b>ADN packing group</b>	Not applicable.

### 14.5. Environmental hazards

<b>Dangerous for the environment</b>	No.
<b>Marine pollutant</b>	No
<b>Other information</b>	No supplementary information available

### 14.6. Special precautions for user

<b>ADR transport category</b>	3
<b>Emergency Action Code</b>	•3YE
<b>Hazard Identification Number (ADR/RID)</b>	30
<b>Tunnel restriction code</b>	(D/E)
<b>Special provisions (ADR)</b>	640E
<b>Limited quantities (ADR)</b>	5L
<b>Excepted quantities (ADR)</b>	E1
<b>Classification code (ADR)</b>	F1
<b>Mixed packing provisions (ADR)</b>	MP19
<b>Packing instructions (ADR)</b>	P001, IBC03, LP01, R001

## KÖSTER Ultraflex-2K A Component

Special provisions for carriage - Packages (ADR)	V12
Special provisions for carriage - Operation (ADR)	S2
Orange plates	30 1139
Limited quantities (IMDG)	5L
Excepted quantities (IMDG)	E1
Special provisions (IMDG)	955
Packing instructions (IMDG)	P001, LP01
IBC packing instructions (IMDG)	IBC03
Tank instructions (IMDG)	T2
Tank special provisions (IMDG)	TP1
EmS-No. (Fire)	F-E
EmS-No. (Spillage)	S-E
Stowage category (IMDG)	A
Excepted quantities (IATA)	E1
Limited quantities (IATA)	10L
PCA Excepted quantities (IATA)	Y344
PCA packing instructions (IATA)	355
PCA max net quantity (IATA)	60L
CAO packing instructions (IATA)	366
CAO max net quantity (IATA)	220L
Special provisions (IATA)	A3
ERG code (IATA)	3L

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Uygulanamaz

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## KÖSTER Ultraflex-2K A Component

**National regulations** EH40/2005 Workplace exposure limits.  
Health and Safety at Work etc. Act 1974 (as amended).  
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### **SECTION 16: Other information**

<b>Issued by</b>	Mazlum Budak Sertifikalı GBF hazırlayıcısı Sertifika No: GBF01.35.06 Sertifika alım tarihi: 06.07.2019
<b>Revision date</b>	29/07/2020
<b>Revision</b>	1,0
<b>Supersedes date</b>	05/11/2019
<b>SDS number</b>	5101
<b>Hazard statements in full</b>	H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H373 May cause damage to organs through prolonged or repeated exposure if swallowed or if inhaled.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.