

T704 / 1111.ENG

KÖSTER® Quellband 2520

Water swellable joint tape on sodium bentonite base

Product Description:

Turkish brand name > KÖSTER Quellband 2520

KÖSTER Quellband 2520 is a sodium bentonite based water swellable joint tape with an alkalinity activated surface coating which stops premature swelling of the tape on the building site.

KÖSTER Quellband 2520 is used as a waterstop in concrete construction joints. The tape is supplied as a robust strip and is simply fastened onto an existing joint face before the next concrete pour. Any subsequent water leakage through the joint activates the tape, which takes up leak water and swells. KÖSTER Quellband 2520 is tested upto 7 bar water pressure.



In comparison to plastic or resin based swellable tapes, which do not alter their structure during swelling, KÖSTER Quellband 2520 breaks down during the swelling process and the resulting paste seals all cracks and voids permenantly.

KÖSTER Quellband 2520 is suitable to be used in potable water tanks. The tape also has a limited swell in seawater tanks and water treatment plants.

The tape is easy to use and has a non-sticky surface, even at high temperatures in the sommer.

Application is very easy, the tape is nailed down on the concrete joint.

Applications:

KÖSTER Quellband 2520 can be used in horizontal and vertical joints.

Horizontal joints ; flor/flor, flor/wall, wall/ceiling and ceiling/ceiling joints

Vertical joints; wall/wall

Advantages:

- Alkalinity activated stops premature swelling on water contact
- Easy application
- No special tools are needed
- High swelling capacity
- Permenant seal of the joint after swelling
 fills all voids and cracks in the concrete
- · High stability works even after years

Instructions:

Surface Preparation - Surfaces shall not be below 5°C and must be clean, dry, structurally sound and free of efflorescence, grease, oil, form release agents and curing compounds.

Application – KÖSTER Quellband needs to be covered with at least 8 cm concrete on all sides to reach the necessary expansion pressure.

The tape must be fixed in the middle of the joints and should not be able to move during pouring of concrete.



T704 / 1111.FNG

Packaging:

KÖSTER Quellband 2520

6 x 5 mt roll / ctn



Storage:


Dry and at room temperature, in original containers.

Shelf Life:

18 months.



KÖSTER Quellband before and after



Typical application detail in joint

Legal Notes: This guide has been issued to provide details regarding the use and application of our products, which can be used in very wide and various areas and to demonstrate the general technical details. This information reflects the knowledge and expertise of our company and is of recommendation nature. Especially, the details regarding implementation and final use are provided with good will to cover the storage, handling and application of our products under normal and recommended conditions. Products, application surfaces, areas and application conditions vary in practice. Therefore, it is of utmost importance to make sure you are applying the right product, at the right conditions and places. Since KÖSTER cannot check how its products are used, it does not accept any responsibility regarding the results of the application and does not provide any guarantees. Information provided here or written/verbal information provided by KÖSTER employees should solely be considered as recommendation. KÖSTER employees to visit the application area do not create any supervisor responsibilities on our part. The product users (user) should test the suitability of the product they are planning to use for the respective application and purpose. KÖSTER has the right to modify its products without announcement. Acceptance of all orders is based on our current sale and transportation terms and conditions. Users should act cautious and observe and protect their own interests and property rights. They are even obliged to act in this manner. This guide only covers KÖSTER products and is not valid for products of other companies. Only the written announcements of our company are valid regarding matters that require technical support provided by us. This technical document is valid until a new version is printed and supersedes all previous versions.

Revision Date: 04-01-2018